

Fristam FKL Positive Displacement Pump Specifications by Model

Model		15	20	25	50	75	150	205	250	400	500	580
Displacement (at max rpm)	gal/rev	0.0155	0.032	0.056	0.096	0.156	0.259	0.45	0.54	0.74	1.29	1.82
	gpm	15.5	25.6	33.6	57.6	93.6	155	270	324	444	516	728
	l/min	58.7	96.9	127.2	218	354	588	1022	1226	1681	1953	2756
	m³/hr	3.5	5.8	7.6	13.1	21.3	35.3	61.3	73	100	117	165
Speed (max)	rpm	1000	800	600	600	600	600	600	600	600	400	400
Pressure (max)	psi	200	200	300	500	500	500	500	500	500	400	300
	bar	14	14	21	35	35	35	35	35	35	28	21
Fittings												
Housing		1.5" clamp	1.5" clamp	1.5" clamp	2.5" clamp	2.5" clamp	3" clamp	4" clamp	4" clamp	6" clamp	6" clamp	6" clamp
Seal Flush Thread		1/16" NPT	1/16" NPT	1/16" NPT	1/16" NPT	1/16" NPT	1/16" NPT	1/16" NPT	1/16" NPT	1/16" NPT	1/8" NPT	1/8" NPT
Weight (complete pump)	lbs	75	75	104	135	360	451	680	744	950	1230	1580
	kg	34	34	47	61	163	205	308	338	431	558	717
Special Options												
Rectangular Inlet		N/A	N/A	N/A	Yes	Yes	Yes	Yes	Yes	Yes	N/A	N/A
O-Ring Seal		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	N/A	N/A	N/A



Fristam Pumps USA
 2410 Parview Road
 Middleton, WI 53562-2521 USA
 Ph: +1 800 841 5001
 Email: fristam@fristampumps.com
 Web: www.fristam.com/usa